

# ► EKM SERIES ELASTOMER COUPLING (CONT.)



## Technical data/Dimensions, continued

Size EKM	Nominal Torque	Elastomer Hardness Shore	Moment of Inertia	Torsion Resistance	Max. Lateral Misalignment	Mass kg (lbs)	Screw Size	Torque to Tighten Screws	Outer Diameter mm (inch)	Length mm (inch)	Bore Range	
	Nm (lb-in)		10 <sup>-3</sup> kgm <sup>2</sup> (lb-in <sup>2</sup> )	Nm/arcmin (lb-ft/Deg)	mm (inch)			Nm (lb-in)			mm (inch)	min. mm (inch)
EKM-500	500	98 Sh-A	2.2	5.8	0.15	1.5	M12	115	100	94	38	56
	(4429)		(7.5)	(257.4)	(0.006)			(3.3)				
EKM-700	700	98 Sh-A	5.2	8	0.15	2.5	M14	185	120	109	40	70
	(6200)		(17.73)	(354.00)	(0.006)			(5.5)				
EKM-1000	1000	72 Sh-D	5.2	12	0.1	2.5	M14	185	120	109	48	70
	(8851)		(17.73)	(531)	(0.004)			(5.5)				

Coupling must be selected so nominal torque is higher than highest operational torque of the application (i.e., during acceleration). Bore diameters smaller than the minimum are possible but reliable transmission of nominal torque cannot be guaranteed.

# ► EKZ SERIES ELASTOMER/DRIVE SHAFT COUPLING



## Major Features

- Special design makes “one person assembly” possible, even with an extremely long intermediate pipe.
- During maintenance, can be exchanged without disassembling the drive or output units.
- Elastomer spider compensates for small shaft misalignments.
- Electronically insulating and dampens oscillation resonance.
- The frictional shaft-hub connection is backlash free and ensures a safe torque transfer without keyways.

## Material

- Aluminum shaft and hubs; polyurethane 72 Shore D spider

## Technical data/Dimensions

Size EKZ	Nominal Torque	Moment of Inertia at 1.0 m	Torsional Stiffness at 1.0 m	Mass at 1.0 m	Screw Size	Torque to Tighten Screws	Outer Diameter mm (inch)	Minimum Length mm (inch)	Bore Range	
	Nm (lb-in)	10 <sup>-3</sup> kgm <sup>2</sup> (lb-in <sup>2</sup> )	Nm/arcmin (lb-ft/Deg)	kg (lbs)		Nm (lb-in)			mm (inch)	min. mm (inch)
EKZ-20	20	0.1	.07	0.8	M5	8	40	132	10	19
	(177)	(0.34)	(3.1)	(1.8)		(71)				
EKZ-45	45	0.36	.19	1.6	M6	14	50	152	13	26
	(399)	(1.22)	(8.4)	(3.5)		(124)				
EKZ-90	90	0.54	0.23	1.9	M8	35	60	160	15	29
	(797)	(1.83)	(10.2)	(4.2)		(310)				
EKZ-200	200	1.1	0.4	2.5	M10	67	70	186	22	33
	(1772)	(3.73)	(17.7)	(5.5)		(593)				
EKZ-400	400	3.2	1.0	3.9	M12	115	85	220	30	42
	(3543)	(10.9)	(44.3)	(8.6)		(1019)				
EKZ-700	700	12.5	2.5	8.1	M14	185	120	284	40	70
	(6200)	(42.4)	(110.6)	(17.8)		(1639)				

Coupling must be selected so nominal torque is higher than highest operational torque of the application (i.e., during acceleration). Bore diameters smaller than the minimum are possible but reliable transmission of nominal torque cannot be guaranteed.